



Technical Data Sheet

MARINE H 1240

Product Description

GR Περιγραφή Προϊόντος: Λιπαντικό υψηλής τεχνολογίας, ειδικά σχεδιασμένο για πετρελαιοκινητήρες ταχύπλων σκαφών υψηλών απαιτήσεων με εμβολοφόρους κινητήρες. Προσφέρει ανώτερη προστασία και εξαιρετική απόδοση σε κινητήρες αλιευτικών σκαφών, παρακτίων ταχυπλών και σκαφών ακτοπλοΐας.

EN Product Description: High-technology lubricant, specifically formulated for heavy-duty, high-speed marine diesel trunk piston engines. It provides superior protection and outstanding performance for fishing vessels, coastal craft, and short-sea shipping lines.

Performance & Specifications

SAE 40

TBN 12

Product Packaging

5201104 20-20L

5201104 204 -204L

Property	Method	Unit		
SAE			30	40
Specific Gravity 15°C	ASTM D 1298	kg/L	0.88	0,88
Viscosity at 40°C	ASTM D 445	cSt		
Viscosity at 100°C	ASTM D 445	cSt	9,30 – 12,50	12,50 – 16,30
Viscosity Index	-	cSt	>100	>100
Pour Point	ASTM D 97	°C	<-15	<-15
Flash Point	ASTM D 92	°C	>220	>220
Total Base Numb	ASTM D 2896	mgKOH/g	>12	>12

Disclaimer: The information contained in this document is based upon data believed to be reliable and relates only to the matters specifically mentioned in this document. Although DYNAMIC KOTE motor oil has used reasonable skill and care in the preparation of this information as of the date below, in the absence of any overriding obligations arising under a specific contract to supply goods or services: no representation, warranty (express or implied), or guarantee is made as to the suitability, accuracy, reliability or completeness of the information; nothing in this document shall reduce the user's responsibility to satisfy itself as to the suitability, accuracy, reliability, and completeness of such information for its particular use; there is no warranty against intellectual property infringement; and DYNAMIC KOTE motor oil shall not be liable for any loss, damage or injury that may occur from the use of this information other than death or personal injury caused by its negligence. No statement shall be construed as an endorsement of any product or process. For greater certainty, before use, particularly if the product is used for a purpose or under conditions which are abnormal or not reasonably foreseeable, this information must be reviewed with the supplier.

Τα άνωθι χαρακτηριστικά αντιπροσωπεύουν τυπικές τιμές.

DYNAMIC KOTE : 01.04.15

© copyright DYNAMIC KOTE motor oil motor oil-DYNAMIC KOTE LUBRICANTS P.C. – OT2B Industrial Zone of ALEXANDROYPOLIS – Greece (Hellas) - GR-68100 – website:

www.dynamickote.eu

