Technical Data Sheet
SHPD SS-HS 15W-40

Product Description

This is a high-performance E7 mineral diesel engine oil formulated to deliver reliable performance in a broad range of heavy-duty applications. It is suitable for low-emission engines (Euro II, Euro III and some Euro IV engines).

Meets the requirements of
SHPD SS-HS 15W-40
SAE 15W-40 API: CI-4, ACEA: E7 ;
Meets the requirements of: MB 228.3, MAN 3275, VOLVO VDS-3, MTU 2.0, RENAULT RLD-2, DEUTZ DQC-II/III, MACK EO-M+/EO-N, CUMMINS 20077/78, CAT ECF-1a/ECF-2, DDC 93K215, JASO DH-1, GLOBAL DHD-1

Product Packaging

5200403 20 -20L
5200403 60 -60L
5200403 204 -204L

Property	Method	Unit	
SAE			15W-40
Specific Gravity 15ºC	ASTM D 1298	kg/L	0,88
Viscosity at 40ºC	ASTM D 445	cSt	
Viscosity at 100ºC	ASTM D 445	cSt	12,5 – 16,3
Viscosity Index	-	cSt	>130
Pour Point	ASTM D 97	ºC	<-30
Flash Point	ASTM D 92	ºC	>220
Total Base Numb	ASTM D 2896	mgKOH/g	>10

Disclaimer: The information contained in this document is based upon data believed to be reliable and relates only to the matters specifically mentioned in this document. Although DYNAMIC KOTE motor oil has used reasonable skill and care in the preparation of this information as of the date below, in the absence of any overriding obligations arising under a specific contract to supply goods or services: no representation, warranty (express or implied), or guarantee is made as to the suitability, accuracy, reliability or completeness of the information; nothing in this document shall reduce the user's responsibility to satisfy itself as to the suitability, accuracy, reliability, and completeness of such information for its particular use; there is no warranty against intellectual property infringement; and DYNAMIC KOTE motor oil shall not be liable for any loss, damage or injury that may occur from the use of this information other than death or personal injury caused by its negligence. No statement shall be construed as an endorsement of any product or process. For greater certainty, before use, particularly if the product is used for a purpose or under conditions which are abnormal or not reasonably foreseeable, this information must be reviewed with the supplier.

Τα άνωθι χαρακτηριστικά αντιπροσωπεύουν τυπικές τιμές.

DYNAMIC KOTE : 01.04.15

© copyright DYNAMIC KOTE motor oil motor oil-DYNAMIC KOTE LUBRICANTS P.C. – OT2B Industrial Zone of ALEXANDROYPOLIS – Greece (Hellas) - GR-68100 – website: www.dynamickote.eu

ISO 9001 2015 CERTIFIED