Technical Data Sheet
SQ 5W-30

Product Description

Advanced Synthetic Engine Oil
Top-tier 100% synthetic engine oil engineered for maximum protection, superior cleanliness, and fuel efficiency. Its Mid SAPS technology effectively protects particulate filters (DPF/GPF) and catalytic converters, ensuring immediate lubrication right from startup.
Application: Ideal for modern gasoline and diesel engines requiring top-tier performance and durability under the most demanding driving conditions.

SAE 5W-30 Fully Synthetic
API SQ/SP/SN ACEA C2/C3-21
Meets the requirements of:
MB 229.51 / 229.52, FIAT 9.55535-S1 / S3, BMW LL-04, Opel OV 040 1547,
dexos®2, GM LL-B-025 / LL-A-025, Renault RN0700 / RN0710,
VW 505 00 / 505 01, Ford WSS-M2C917-A

Product Packaging

5200152 1 -12X1L
5200152 5 -4X5L
5200152 204 -204L

Property	Method	Unit	
SAE			5W-30
Specific Gravity 15ºC	ASTM D 1298	kg/L	0,85
Viscosity at 40ºC	ASTM D 445	cSt	60 - 72
Viscosity at 100ºC	ASTM D 445	cSt	9,3-12,5
Viscosity Index	-	cSt	160 - 175
Pour Point	ASTM D 97	ºC	MAX -36C
Flash Point	ASTM D 92	ºC	210 – 240 ºC
Total Base Numb	ASTM D 2896	mgKOH/g	7,0 – 8,5

Disclaimer: The information contained in this document is based upon data believed to be reliable and relates only to the matters specifically mentioned in this document. Although DYNAMIC KOTE motor oil has used reasonable skill and care in the preparation of this information as of the date below, in the absence of any overriding obligations arising under a specific contract to supply goods or services: no representation, warranty (express or implied), or guarantee is made as to the suitability, accuracy, reliability or completeness of the information; nothing in this document shall reduce the user's responsibility to satisfy itself as to the suitability, accuracy, reliability, and completeness of such information for its particular use; there is no warranty against intellectual property infringement; and DYNAMIC KOTE motor oil shall not be liable for any loss, damage or injury that may occur from the use of this information other than death or personal injury caused by its negligence. No statement shall be construed as an endorsement of any product or process. For greater certainty, before use, particularly if the product is used for a purpose or under conditions which are abnormal or not reasonably foreseeable, this information must be reviewed with the supplier.

Τα άνωθι χαρακτηριστικά αντιπροσωπεύουν τυπικές τιμές.

DYNAMIC KOTE : 01.04.15

© copyright DYNAMIC KOTE motor oil motor oil-DYNAMIC KOTE LUBRICANTS P.C. – OT2B Industrial Zone of ALEXANDROYPOLIS – Greece (Hellas) - GR-68100 – website: www.dynamickote.eu

ISO 9001 2015 CERTIFIED