



Technical Data Sheet AGRO STOU 15W-40

Product Description

Universal multigrade oil for engines, transmissions, wet brakes and hydraulic systems of agricultural tractors.
Super Tractor Oil Universal

Meets the requirements of

AGRO STOU 15W-40

SAE 15W-40 API:GL-4/CG-4/CF-4, John Deere J20C, Allison C-4

Ford M2C 159B/134D, Part II CAT T0-2,

N.Holland MAT 3525 & 3526, ZF TE ML 06B/07B

Massey Ferguson CMS M1143 & M1135

MF CMS M1143/M1144/M1135/M1139,

Product Packaging

5200701 4 -4X4L

5200701 10 – 10L

5200701 20 -20L

5200701 204 -204L

Property	Method	Unit	15W-40	10W-30
SAE			15W-40	10W-30
Specific Gravity 15°C	ASTM D 1298	kg/L	0,88	0,875
Viscosity at 40°C	ASTM D 445	cSt		
Viscosity at 100°C	ASTM D 445	cSt	12,5 – 16,3	9,3 – 12,5
Viscosity Index	-	cSt	>120	>120
Pour Point	ASTM D 97	°C	<-25	<-30
Flash Point	ASTM D 92	°C	>210	>215
Total Base Numb	ASTM D 2896	mgKOH/g	>10	>10

Disclaimer: The information contained in this document is based upon data believed to be reliable and relates only to the matters specifically mentioned in this document. Although DYNAMIC KOTE motor oil has used reasonable skill and care in the preparation of this information as of the date below, in the absence of any overriding obligations arising under a specific contract to supply goods or services: no representation, warranty (express or implied), or guarantee is made as to the suitability, accuracy, reliability or completeness of the information; nothing in this document shall reduce the user's responsibility to satisfy itself as to the suitability, accuracy, reliability, and completeness of such information for its particular use; there is no warranty against intellectual property infringement; and DYNAMIC KOTE motor oil shall not be liable for any loss, damage or injury that may occur from the use of this information other than death or personal injury caused by its negligence. No statement shall be construed as an endorsement of any product or process. For greater certainty, before use, particularly if the product is used for a purpose or under conditions which are abnormal or not reasonably foreseeable, this information must be reviewed with the supplier.

Τα άνωθι χαρακτηριστικά αντιπροσωπεύουν τυπικές τιμές.

DYNAMIC KOTE : 01.04.15

© copyright DYNAMIC KOTE motor oil motor oil-DYNAMIC KOTE LUBRICANTS P.C. – OT2B Industrial Zone of ALEXANDROYPOLIS – Greece (Hellas) - GR-68100 – website:

www.dynamickote.eu

