



## Technical Data Sheet AGRO-X 20W-30

### Product Description

Designed for automatic transmissions, hydraulic systems, brakes and clutches of tractors, forklifts and off-road equipment. This oil (Universal Tractor Transmission Oil) should never be used to lubricate the engine. When the manufacturer requires an oil for the lubrication of all parts including the engine, he refers to a super tractor oil universal.

Universal Tractor Transmission Oil

Meets the requirements of

AGRO-X UTTO 20W-30

SAE 20W-30 API:GL-4/CG-4/CF-4,John Deere J20C,Allison C-4

Ford M2C 159B/134D, Part II CAT T0-2,

N.Holland MAT 3525 & 3526, ZF TE ML 06B/07B

Massey Ferguson CMS M1143 & M1135

MF CMS M1143/M1144/M1135/M1139,

### Product Packaging

5200710 4 -4X4L

5200710 10 – 10L

5200710 20 -20L

5200710 204 -204L

Property	Method	Unit	20W-30	10W-30
SAE			20W-30	10W-30
Specific Gravity 15°C	ASTM D 1298	kg/L	0,88	0,875
Viscosity at 40°C	ASTM D 445	cSt	85	70
Viscosity at 100°C	ASTM D 445	cSt	9,3 – 12,5	9,3 – 12,5
Viscosity Index	-	cSt	>110	>125
Pour Point	ASTM D 97	°C	<-30	<-30
Flash Point	ASTM D 92	°C	>215	>215
Total Base Numb	ASTM D 2896	mgKOH/g	>8,5	>8,5

Disclaimer: The information contained in this document is based upon data believed to be reliable and relates only to the matters specifically mentioned in this document. Although DYNAMIC KOTE motor oil has used reasonable skill and care in the preparation of this information as of the date below, in the absence of any overriding obligations arising under a specific contract to supply goods or services: no representation, warranty (express or implied), or guarantee is made as to the suitability, accuracy, reliability or completeness of the information; nothing in this document shall reduce the user's responsibility to satisfy itself as to the suitability, accuracy, reliability, and completeness of such information for its particular use; there is no warranty against intellectual property infringement; and DYNAMIC KOTE motor oil shall not be liable for any loss, damage or injury that may occur from the use of this information other than death or personal injury caused by its negligence. No statement shall be construed as an endorsement of any product or process. For greater certainty, before use, particularly if the product is used for a purpose or under conditions which are abnormal or not reasonably foreseeable, this information must be reviewed with the supplier.

Τα άνωθι χαρακτηριστικά αντιπροσωπεύουν τυπικές τιμές.

DYNAMIC KOTE : 01.04.15

© copyright DYNAMIC KOTE motor oil motor oil-DYNAMIC KOTE LUBRICANTS P.C. – OT2B Industrial Zone of ALEXANDROYPOLIS – Greece (Hellas) - GR-68100 – website:

[www.dynamickote.eu](http://www.dynamickote.eu)

