

Technical Data Sheet ATF D-II

Product Description

It can be used in automatic transmissions, torque convertors, power steering and hydraulic circuits.

Meets the requirements of ATF D-II Dexron IID,IIE MB 236.6, Allison C3, MAN 339 type C, Type A Suffix A (TASA),

Product Packaging

5200903 1 -12X1L 5200903 20 -20L 5200903 204 -204L

Color

Property	Method	Unit	
			ATF D-II
Specific Gravity 15°C	ASTM D 1298	kg/L	0,87
Viscosity at 40°C	ASTM D 445	cSt	
Viscosity at 100°C	ASTM D 445	cSt	7 – 7,8
Viscosity Index	-	cSt	>100
Pour Point	ASTM D 97	°C	<-10
Flash Point	ASTM D 92	°C	>200

Disclaimer: The information contained in this document is based upon data believed to be reliable and relates only to the matters specifically mentioned in this document. Although DYNAMIC KOTE motor oil has used reasonable skill and care in the preparation of this information as of the date below, in the absence of any overriding obligations arising under a specific contract to supply goods or services: no representation, warranty (express or implied), or guarantee is made as to the suitability, accuracy, reliability, accuracy, reliability or completeness of the information rothing in this document shall reduce the user's responsibility to satisfy itself as to the suitability, accuracy, reliability, and completeness of such information for its particular use; there is no warranty against intellectual property infringement; and DYNAMIC KOTE motor oil shall not be liable for any loss, damage or injury that may occur from the use of this information other than death or personal injury caused by its negligence. No statement shall be construed as an endorsement of any product or process. For greater certainty, before use, particularly if the product is used for a purpose or under conditions which are abnormal or not reasonably foreseeable, this information must be reviewed with the supplier.

Red

Τα άνωθι χαρακτηριστικά αντιπροσωπεύουν τυπικές τιμές.

DYNAMIC KOTE: 01.04.15

