



## Technical Data Sheet HYDRO-POC VG 32

### Product Description

A high viscosity index hydraulic oil, based on selected ingredients, specifically intended for use in hydraulic circuits. It also demonstrates good filterability, water separation, and quick air release.

Meets the requirements of  
Hydro-POC VG32 DIN 51524, Part III HVLP  
Afnor NF E 48-603

### Product Packaging

5200519 20 -20L  
5200519 204 -204L

Property	Method	Unit	32	46	68	100
ISO			32	46	68	100
Specific Gravity 15°C	ASTM D 1298	kg/L	0,87	0,875	0,88	0,89
Viscosity at 40°C	ASTM D 445	cSt	28,8 – 35,20	41,4 – 50,6	61,2 – 74,8	90 – 110
Viscosity at 100°C	ASTM D 445	cSt				
Viscosity Index	-	cSt	>110	>110	>110	>110
Pour Point	ASTM D 97	°C	<-30	<-30	<-30	<-30
Flash Point	ASTM D 92	°C	>220	>220	>230	>235
Color	Crystal Gold		Crystal Gold	Crystal Gold	Crystal Gold	Crystal Gold

Disclaimer: The information contained in this document is based upon data believed to be reliable and relates only to the matters specifically mentioned in this document. Although DYNAMIC KOTE motor oil has used reasonable skill and care in the preparation of this information as of the date below, in the absence of any overriding obligations arising under a specific contract to supply goods or services: no representation, warranty (express or implied), or guarantee is made as to the suitability, accuracy, reliability or completeness of the information; nothing in this document shall reduce the user's responsibility to satisfy itself as to the suitability, accuracy, reliability, and completeness of such information for its particular use; there is no warranty against intellectual property infringement; and DYNAMIC KOTE motor oil shall not be liable for any loss, damage or injury that may occur from the use of this information other than death or personal injury caused by its negligence. No statement shall be construed as an endorsement of any product or process. For greater certainty, before use, particularly if the product is used for a purpose or under conditions which are abnormal or not reasonably foreseeable, this information must be reviewed with the supplier.

Τα άνωθι χαρακτηριστικά αντιπροσωπεύουν τυπικές τιμές.

DYNAMIC KOTE : 01.04.15

© copyright DYNAMIC KOTE motor oil motor oil-DYNAMIC KOTE LUBRICANTS P.C. – OT2B Industrial Zone of ALEXANDROYPOLIS – Greece (Hellas) - GR-68100 – website:

[www.dynamickote.eu](http://www.dynamickote.eu)

