



Technical Data Sheet MGL-4 80W

Product Description

Gear oil for mechanical transmissions with moderate “extreme pressure” characteristics and is specifically developed to avoid corrosion of copper alloys.

Meets the requirements of
MGL-4 80W
SAE 80 API: GL-4

Product Packaging

5200811 1 -12X1L
5200811 4 -4X4L
5200811 20 -20L
5200811 204 -204L

Property	Method	Unit	80W-90	90	80W
SAE			80W-90	90	80W
Specific Gravity 15°C	ASTM D 1298	kg/L	0,88	0.88	0.875
Viscosity at 40°C	ASTM D 445	cSt			
Viscosity at 100°C	ASTM D 445	cSt	13,5 – 18,5	13,5 – 18,5	7 – 11
Viscosity Index	-	cSt	>110	>100	>100
Pour Point	ASTM D 97	°C	<-20	<-10	<-20
Flash Point	ASTM D 92	°C	>200	>200	>200
Color			Crystal Gold	Crystal Gold	Crystal Gold

Disclaimer: The information contained in this document is based upon data believed to be reliable and relates only to the matters specifically mentioned in this document. Although DYNAMIC KOTE motor oil has used reasonable skill and care in the preparation of this information as of the date below, in the absence of any overriding obligations arising under a specific contract to supply goods or services: no representation, warranty (express or implied), or guarantee is made as to the suitability, accuracy, reliability or completeness of the information; nothing in this document shall reduce the user's responsibility to satisfy itself as to the suitability, accuracy, reliability, and completeness of such information for its particular use; there is no warranty against intellectual property infringement; and DYNAMIC KOTE motor oil shall not be liable for any loss, damage or injury that may occur from the use of this information other than death or personal injury caused by its negligence. No statement shall be construed as an endorsement of any product or process. For greater certainty, before use, particularly if the product is used for a purpose or under conditions which are abnormal or not reasonably foreseeable, this information must be reviewed with the supplier.

Τα άνωθι χαρακτηριστικά αντιπροσωπεύουν τυπικές τιμές.

DYNAMIC KOTE : 01.04.15

© copyright DYNAMIC KOTE motor oil motor oil-DYNAMIC KOTE LUBRICANTS P.C. – OT2B Industrial Zone of ALEXANDROYPOLIS – Greece (Hellas) - GR-68100 – website:

www.dynamickote.eu

