



Technical Data Sheet SHPDO FM 15W-40

Product Description

Universal engine oil, designed to meet the latest specifications of both European and American manufacturers of heavy diesel engines. This oil is suitable for low-emission engines (Euro II and Euro III and some Euro IV engines); it is not suitable for Euro IV engines with particulate filter.

Meets the requirements of

SHPDO FM 15W-40

SHPDO FM 15W-40 API:CG-4/CF-4/CF/SL

SAE 15W-40 ACEA: E2, API: CG-4/SJ, MB 228.3,

Volvo VDS, MAN M3275-1 & MTU Type 2

Product Packaging

5200410 20 -20L

5200410 60 -60L

5200410 204 -204L

Property	Method	Unit	15W-40	20W-50
SAE			15W-40	20W-50
Specific Gravity 15°C	ASTM D 1298	kg/L	0,88	0,89
Viscosity at 40°C	ASTM D 445	cSt		
Viscosity at 100°C	ASTM D 445	cSt	12,5 – 16,3	16,3 – 21,9
Viscosity Index	-	cSt	>115	>115
Pour Point	ASTM D 97	°C	<-20	<-20
Flash Point	ASTM D 92	°C	>220	>220
Total Base Numb	ASTM D 2896	mgKOH/g	>8	>8

Disclaimer: The information contained in this document is based upon data believed to be reliable and relates only to the matters specifically mentioned in this document. Although DYNAMIC KOTE motor oil has used reasonable skill and care in the preparation of this information as of the date below, in the absence of any overriding obligations arising under a specific contract to supply goods or services: no representation, warranty (express or implied), or guarantee is made as to the suitability, accuracy, reliability or completeness of the information; nothing in this document shall reduce the user's responsibility to satisfy itself as to the suitability, accuracy, reliability, and completeness of such information for its particular use; there is no warranty against intellectual property infringement; and DYNAMIC KOTE motor oil shall not be liable for any loss, damage or injury that may occur from the use of this information other than death or personal injury caused by its negligence. No statement shall be construed as an endorsement of any product or process. For greater certainty, before use, particularly if the product is used for a purpose or under conditions which are abnormal or not reasonably foreseeable, this information must be reviewed with the supplier.

Τα άνωθι χαρακτηριστικά αντιπροσωπεύουν τυπικές τιμές.

DYNAMIC KOTE : 01.04.15

© copyright DYNAMIC KOTE motor oil motor oil-DYNAMIC KOTE LUBRICANTS P.C. – OT2B Industrial Zone of ALEXANDROYPOLIS – Greece (Hellas) - GR-68100 – website: www.dynamickote.eu

