



Technical Data Sheet SP 0W-20

Product Description

This synthetic MID SAPS ACEA C5 lubricant meets the new fuel economy specification . The very low viscosity grade SAE 0W20 enables the engine to run at very high fuel-efficiency. This engine oil optimizes wear protection and engine cleanliness.

Meets the requirements of

SP 0W-20 Fully Synthetic DPF Motor Oil
SAE 0W-20
API SP/SN PLUS/SN ACEA C5-21 ILSAC GF-6A
FORD WSS-M2C962-A1

Product Packaging

5200106 1 -12X1L
5200106 4 -4X4L
5200106 5 -4X5L
5200106 60 -60L
5200106 204 -204L

Property	Method	Unit	
SAE			0W-20
Specific Gravity 15°C	ASTM D 1298	kg/L	0,83
Viscosity at 40°C	ASTM D 445	cSt	
Viscosity at 100°C	ASTM D 445	cSt	5.6 – 9.3
Viscosity Index	-	cSt	>140
Pour Point	ASTM D 97	°C	<-40
Flash Point	ASTM D 92	°C	>200
Total Base Numb	ASTM D 2896	mgKOH/g	>6,5

Disclaimer: The information contained in this document is based upon data believed to be reliable and relates only to the matters specifically mentioned in this document. Although DYNAMIC KOTE motor oil has used reasonable skill and care in the preparation of this information as of the date below, in the absence of any overriding obligations arising under a specific contract to supply goods or services: no representation, warranty (express or implied), or guarantee is made as to the suitability, accuracy, reliability or completeness of the information; nothing in this document shall reduce the user's responsibility to satisfy itself as to the suitability, accuracy, reliability, and completeness of such information for its particular use; there is no warranty against intellectual property infringement; and DYNAMIC KOTE motor oil shall not be liable for any loss, damage or injury that may occur from the use of this information other than death or personal injury caused by its negligence. No statement shall be construed as an endorsement of any product or process. For greater certainty, before use, particularly if the product is used for a purpose or under conditions which are abnormal or not reasonably foreseeable, this information must be reviewed with the supplier.

Τα άνωθι χαρακτηριστικά αντιπροσωπεύουν τυπικές τιμές.

DYNAMIC KOTE : 01.04.15

© copyright DYNAMIC KOTE motor oil motor oil-DYNAMIC KOTE LUBRICANTS P.C. – OT2B Industrial Zone of ALEXANDROYPOLIS – Greece (Hellas) - GR-68100 – website: www.dynamickote.eu

