



Technical Data Sheet TURBO S 32 Turbine Oil

Product Description

High quality lubricant for steam and gas turbines. It has excellent antioxidant and anti-foaming properties.

Meets the requirements of

TURBO S 32

DIN 51515, Part I, Siemens TLV 9013 04/01,

BS 489, Brown Boveri HTGD 90117,

General Electric GEK 32568 A/C, US.Steel 120,

MIL-L-17672 D, GEGB Standard 207001,

Westinghouse Electric Corp. Turbine Oil Spec.

Product Packaging

5201005 20 -20L

5201005 204 -204L

Property	Method	Unit		
ISO			22	32
Specific Gravity 15°C	ASTM D 1298	kg/L	0.85	0,87
Viscosity at 40°C	ASTM D 445	cSt	19,8 – 24,2	28,8 – 35,20
Viscosity at 100°C	ASTM D 445	cSt		
Viscosity Index	-	cSt	>100	>100
Pour Point	ASTM D 97	°C	<-16	<-16
Flash Point	ASTM D 92	°C	>200	>205
Color	Crystal Gold		Crystal Gold	Crystal Gold

Disclaimer: The information contained in this document is based upon data believed to be reliable and relates only to the matters specifically mentioned in this document. Although DYNAMIC KOTE motor oil has used reasonable skill and care in the preparation of this information as of the date below, in the absence of any overriding obligations arising under a specific contract to supply goods or services: no representation, warranty (express or implied), or guarantee is made as to the suitability, accuracy, reliability or completeness of the information; nothing in this document shall reduce the user's responsibility to satisfy itself as to the suitability, accuracy, reliability, and completeness of such information for its particular use; there is no warranty against intellectual property infringement; and DYNAMIC KOTE motor oil shall not be liable for any loss, damage or injury that may occur from the use of this information other than death or personal injury caused by its negligence. No statement shall be construed as an endorsement of any product or process. For greater certainty, before use, particularly if the product is used for a purpose or under conditions which are abnormal or not reasonably foreseeable, this information must be reviewed with the supplier.

Τα άνωθι χαρακτηριστικά αντιπροσωπεύουν τυπικές τιμές.

DYNAMIC KOTE : 01.04.15

© copyright DYNAMIC KOTE motor oil motor oil-DYNAMIC KOTE LUBRICANTS P.C. – OT2B Industrial Zone of ALEXANDROYPOLIS – Greece (Hellas) - GR-68100 – website:

www.dynamickote.eu

