



## Technical Data Sheet DX 1 5W-30

### Product Description

DX 1 5W-30 100% HC synthetic has been specifically developed to meet the challenging requirements of the latest GM Dexos1 Gen 3 specification and ILSAC GF-6 A standard where fuel economy and CO2 reduction are important. It provides the performance needed for the most recent requirements for gasoline-fueled US and Asian passenger cars.

### Meets the requirements of

API SP ILSAC GF6A DEXOS 1  
Gen3 FORD WSS-M2C961-  
A1 CHRYSLER MS-6395

### Product Packaging

5200143 1 -12X1L  
5200143 5 -4X5L  
5200143 20 -20L  
5200143 60 -60L  
5200143 204 -204L

Property	Method	Unit	
SAE			5W-30
Specific Gravity 15°C	ASTM D 1298	kg/L	0,85
Viscosity at 40°C	ASTM D 445	cSt	55 - 82
Viscosity at 100°C	ASTM D 445	cSt	9,3-12,5
Viscosity Index	-	cSt	156 - 169
Pour Point	ASTM D 97	°C	MAX -36C
Flash Point	ASTM D 92	°C	MIN 200C
Total Base Numb	ASTM D 2896	mgKOH/g	8

Disclaimer: The information contained in this document is based upon data believed to be reliable and relates only to the matters specifically mentioned in this document. Although DYNAMIC KOTE motor oil has used reasonable skill and care in the preparation of this information as of the date below, in the absence of any overriding obligations arising under a specific contract to supply goods or services: no representation, warranty (express or implied), or guarantee is made as to the suitability, accuracy, reliability or completeness of the information; nothing in this document shall reduce the user's responsibility to satisfy itself as to the suitability, accuracy, reliability, and completeness of such information for its particular use; there is no warranty against intellectual property infringement; and DYNAMIC KOTE motor oil shall not be liable for any loss, damage or injury that may occur from the use of this information other than death or personal injury caused by its negligence. No statement shall be construed as an endorsement of any product or process. For greater certainty, before use, particularly if the product is used for a purpose or under conditions which are abnormal or not reasonably foreseeable, this information must be reviewed with the supplier.

Τα άνωθι χαρακτηριστικά αντιπροσωπεύουν τυπικές τιμές.

DYNAMIC KOTE : 01.04.15

© copyright DYNAMIC KOTE motor oil motor oil-DYNAMIC KOTE LUBRICANTS P.C. – OT2B Industrial Zone of ALEXANDROYPOLIS – Greece (Hellas) - GR-68100 – website:

[www.dynamickote.eu](http://www.dynamickote.eu)

