



Technical Data Sheet ATF DCTF

Product Description

Dual Clutch Transmission Fluid (DCTF)

Specifically designed for **Dual Clutch Transmissions (DCTF)**, both dry and wet types. It offers top-tier performance and protection for even the most demanding transmission systems.

Why Choose It:

- **Smooth Shifting:** Eliminates vibrations and provides instant response with no torque interruption.
- **Fuel Economy:** Optimizes friction for reduced fuel consumption.
- **Ultimate Protection:** High resistance to wear, corrosion, and extreme temperatures.
- **Cold Start Performance:** Improved gearbox operation even at very low temperatures.

Note: Also suitable for manual gearboxes requiring **SAE 75W** viscosity. Always consult the manufacturer's manual.

Meets the requirements of

BMW Drivelogic 7-speed (Getrag)/DCTF-1
BMW DCTF-1+
BMW DCTF-2
BMW 6-speed DCT
BMW 83 22 2 167 666/MTF LT-5
Borg Warner
Bugatti Veyron
BYD DCTs, Q/BYD-A1909.0058-2013
Castrol BOT 341
Castrol BOT 351 C4
Castrol BOT 351 FE Plus
Castrol BOT 351LV
Castrol BOT 450
Changan DCTF
Chery DCTs
Chrysler 68044345 EA & GA
Chrysler Powershift 6-speed (Getrag)
Eaton PS-278
FAW 7DCT220F
Ferrari 7-speed (Getrag)/TF DCT-3

Disclaimer: The information contained in this document is based upon data believed to be reliable and relates only to the matters specifically mentioned in this document. Although DYNAMIC KOTE motor oil has used reasonable skill and care in the preparation of this information as of the date below, in the absence of any overriding obligations arising under a specific contract to supply goods or services: no representation, warranty (express or implied), or guarantee is made as to the suitability, accuracy, reliability or completeness of the information; nothing in this document shall reduce the user's responsibility to satisfy itself as to the suitability, accuracy, reliability, and completeness of such information for its particular use; there is no warranty against intellectual property infringement; and DYNAMIC KOTE motor oil shall not be liable for any loss, damage or injury that may occur from the use of this information other than death or personal injury caused by its negligence. No statement shall be construed as an endorsement of any product or process. For greater certainty, before use, particularly if the product is used for a purpose or under conditions which are abnormal or not reasonably foreseeable, this information must be reviewed with the supplier.

Τα άνωθι χαρακτηριστικά αντιπροσωπεύουν τυπικές τιμές.

DYNAMIC KOTE : 01.04.15

© copyright DYNAMIC KOTE motor oil motor oil-DYNAMIC KOTE LUBRICANTS P.C. – OT2B Industrial Zone of ALEXANDROYPOLIS – Greece (Hellas) - GR-68100 – website: www.dynamickote.eu





Fiat 9.55550-MZ6
Ford/Nissan Powershift 6-speed (GFT) / Ford WSS-M2C936A, part # 1490763/1490761
Ford WSS-M2C200-D2/ XT-11-QDC
Ford WSS-M2C218-A1, Ford F-DC, part # KU7J M2C218AA
Geely 7 speed
Great Wall DCT
GSMC 7WF35
Hyundai/Kia 04300-2N100, Hyundai 00232-19100 WDCTF Hd G Gear oil
Hyundai/Kia 04300-2N110 WDHO-1, Hyundai 00232-19101 WDCTF Hd H Control oil
JAC DTF630
JF Powertronic: DCT350
Magna/Getrag DCTs
Mitsubishi TC-SST 6-speed (GFT) / MZ320065 DiaQueen SSTF-1
PDK transmissieolie voor ZF (DCT Transmission Oil for ZF)
Peugeot/Citroen DCS 6-speed (GFT)/9734.S2
Porsche 000-043-306-34
Porsche 00004320729
Porsche 999.917.080.01
Punch: DT2
Renault EDC 6-speed (Getrag)
Renault EDC-7
Renault DC4 (BOT 450)
Renault DW5
Renault DW6
SAIC: SHDT 360 & SHDT280
Shell TF DCT-F3
Smart Twinamic
Tsingshan DCT170 DF515 DF727C
Volvo Dual Clutch Oil D1
Volvo Dual Clutch Oil D2
Volvo Powershift 6-speed (GFT)/1161838/1161839
VW/Audi G 052 182
VW/Audi G 052 536
VW/Audi G 055 536
VW/Audi G 052 512 / G 055 512
VW (Audi, Seat, Skoda) 6-speed
VW/Audi TL 52529 (spec)/G 052 529 A2 or A6 (fluid) / DSG7 = S-Tronic 7/7 speed VW (Audi, Seat, Skoda)
VW/Audi G 055 529
VW/Audi TL 521 82 (spec) / G 052 182 A2 or A6 (fluid)
ZF/Porsche Oil #999.917.080.00
ZF DCTs

Disclaimer: The information contained in this document is based upon data believed to be reliable and relates only to the matters specifically mentioned in this document. Although DYNAMIC KOTE motor oil has used reasonable skill and care in the preparation of this information as of the date below, in the absence of any overriding obligations arising under a specific contract to supply goods or services: no representation, warranty (express or implied), or guarantee is made as to the suitability, accuracy, reliability or completeness of the information; nothing in this document shall reduce the user's responsibility to satisfy itself as to the suitability, accuracy, reliability, and completeness of such information for its particular use; there is no warranty against intellectual property infringement; and DYNAMIC KOTE motor oil shall not be liable for any loss, damage or injury that may occur from the use of this information other than death or personal injury caused by its negligence. No statement shall be construed as an endorsement of any product or process. For greater certainty, before use, particularly if the product is used for a purpose or under conditions which are abnormal or not reasonably foreseeable, this information must be reviewed with the supplier.

Τα άνωθι χαρακτηριστικά αντιπροσωπεύουν τυπικές τιμές.

DYNAMIC KOTE : 01.04.15

© copyright DYNAMIC KOTE motor oil motor oil-DYNAMIC KOTE LUBRICANTS P.C. – OT2B Industrial Zone of ALEXANDROYPOLIS – Greece (Hellas) - GR-68100 – website:

www.dynamickote.eu





e-Mobility Claims

Fiat 9.55550-HE2 & Fiat 9.55550-HE3

Lynk & Co. 01 (Plug-in hybrid and Hybrid electric SUV)

Stellantis 1693483780

VW Golf GTE DQ400E

Not to be used for Step-AT or CVT applications

Product Packaging

5200911 1 -12X1L

5200911 20 -20L

5200911 204 -204L

Property	Method	Unit	
			ATF DCTF
Specific Gravity 15°C	ASTM D 1298	kg/L	0,85
Viscosity at 40°C	ASTM D 445	cSt	33 – 36 cSt
Viscosity at 100°C	ASTM D 445	cSt	7.0 – 7.5 cSt
Viscosity Index	-	cSt	~170 – 185
Pour Point	ASTM D 97	°C	-45°C to -51°C
Flash Point	ASTM D 92	°C	220°C – 240°C
Color			Red or Amber

Disclaimer: The information contained in this document is based upon data believed to be reliable and relates only to the matters specifically mentioned in this document. Although DYNAMIC KOTE motor oil has used reasonable skill and care in the preparation of this information as of the date below, in the absence of any overriding obligations arising under a specific contract to supply goods or services: no representation, warranty (express or implied), or guarantee is made as to the suitability, accuracy, reliability or completeness of the information; nothing in this document shall reduce the user's responsibility to satisfy itself as to the suitability, accuracy, reliability, and completeness of such information for its particular use; there is no warranty against intellectual property infringement; and DYNAMIC KOTE motor oil shall not be liable for any loss, damage or injury that may occur from the use of this information other than death or personal injury caused by its negligence. No statement shall be construed as an endorsement of any product or process. For greater certainty, before use, particularly if the product is used for a purpose or under conditions which are abnormal or not reasonably foreseeable, this information must be reviewed with the supplier.

Τα άνωθι χαρακτηριστικά αντιπροσωπεύουν τυπικές τιμές.

DYNAMIC KOTE : 01.04.15

© copyright DYNAMIC KOTE motor oil motor oil-DYNAMIC KOTE LUBRICANTS P.C. – OT2B Industrial Zone of ALEXANDROYPOLIS – Greece (Hellas) - GR-68100 – website:

www.dynamickote.eu

