



Technical Data Sheet ATF CVT

Product Description

Continuously Variable Transmissions

Full synthetic lubricant high quality base oils, that has been designed to be used in most CVT gearboxes. It is suitable for continuously variable transmissions, using steel push-belts or chains. It offers outstanding anti-wear protection and stable friction characteristics.

Meets the requirements of

ATF CVT Fully Synthetic AUDI MULTI TRONIC • BMW MINI COOPER EZL 799/799A • DODGE/JEEP/CHRYSLER NS-2CVT+4 • CVT FLUID J1 • CVT FLUID DFE • DAIHATSU AMMIX CVT FLUID DC • FORD CVT23 HONDA HMMF/HCF-2/Z-1 • MAZDA JWS 3320 • MITSUBISHI CVTF-J1/J4/J4+MMC DIAQUEES ATF SP-III • NISSAN NS-1/NS-2/NS-3 • SUBARU iCVT/FG/ECVT/NS2 SUZUKI CVTF TC/TC 3320/NS2 • SUZUKI CVT FLUID GREEN 1 AND 2/1V • TOYOTA CVT FLUID TC / FE • VW/AUDI TL 521 16 (G 052 516) • VW/AUDI TL 521 80 (G 052 180 A2)

Product Packaging

5200902 1 -12X1L

5200902 20 -20L

5200902 204 -204L

Property	Method	Unit	
			ATF CVT
Specific Gravity 15°C	ASTM D 1298	kg/L	0,85
Viscosity at 40°C	ASTM D 445	cSt	27.5 – 30.0
Viscosity at 100°C	ASTM D 445	cSt	5.7 – 6.1
Viscosity Index	-	cSt	>160
Pour Point	ASTM D 97	°C	<-40
Flash Point	ASTM D 92	°C	>210
Color			Red/Yellow

Disclaimer: The information contained in this document is based upon data believed to be reliable and relates only to the matters specifically mentioned in this document. Although DYNAMIC KOTE motor oil has used reasonable skill and care in the preparation of this information as of the date below, in the absence of any overriding obligations arising under a specific contract to supply goods or services: no representation, warranty (express or implied), or guarantee is made as to the suitability, accuracy, reliability or completeness of the information; nothing in this document shall reduce the user's responsibility to satisfy itself as to the suitability, accuracy, reliability, and completeness of such information for its particular use; there is no warranty against intellectual property infringement; and DYNAMIC KOTE motor oil shall not be liable for any loss, damage or injury that may occur from the use of this information other than death or personal injury caused by its negligence. No statement shall be construed as an endorsement of any product or process. For greater certainty, before use, particularly if the product is used for a purpose or under conditions which are abnormal or not reasonably foreseeable, this information must be reviewed with the supplier.

Τα άνωθι χαρακτηριστικά αντιπροσωπεύουν τυπικές τιμές.

DYNAMIC KOTE : 01.04.15

© copyright DYNAMIC KOTE motor oil motor oil-DYNAMIC KOTE LUBRICANTS P.C. – OT2B Industrial Zone of ALEXANDROYPOLIS – Greece (Hellas) - GR-68100 – website:

www.dynamickote.eu

