



## Technical Data Sheet AGRO-X 10W-30

### Product Description

Designed for automatic transmissions, hydraulic systems, brakes and clutches of tractors, forklifts and off-road equipment. This oil (Universal Tractor Transmission Oil) should never be used to lubricate the engine. When the manufacturer requires an oil for the lubrication of all parts including the engine, he refers to a super tractor oil universal.

Universal Tractor Transmission Oil

Meets the requirements of

AGRO-X UTTO 10W-30

SAE 10W-30 API:GL-4 AGCO 821XL • Allison C2, C3 • Allison C4 • API GL-4 • Caterpillar TO-2 • CNH MAT 3505 • CNH MAT 3510 • CNH MAT 3525 • CNH MAT 3526 • CNH MAT 3540 • Denison HF-0, HF-1, HF-2 (except demulsibility) • Deutz-Allis Power Fluid 821XL, 25741, 25743, 246634, 272843 • Dresser • Fiat Heston AF-87 • Ford ESN-M2C-86 A-C • Ford FNHA-2-C-200 • Ford FNHA-2-C-201 • Ford M2CA-C • Ford ESN-M2C134A-D (NH-410B) • Ford ESN-M2C86A, B, & C • Ford ESN-M2C-41, 41A & B, & 43 • Ford ESN-M2C-48 B & C • Ford ESN-M2C53 A & B • Ford ESN-M2C-77A, 78A, 79A • Ford ESN-M2C-142A • Ford ESN-M2C-143 • Ford ESN-M2C-92A • Ford ESN-M2C-159 A-C • Ford New Holland M4864A & B • Industry of Machinery and Tractors (IMT) • International Harvester Hy-Tran B-6 • Japanese Construction Mechanization Association (JCMAS), HK P-041 & P-042 • J.I. Case Case-O-Matic Type A • JI Case MS-143, 144, 145 International Famall (TCH Fluid) • JI Case MS-185 (TFD Fluid) • JI Case MS1204-1205 (Powergard PFT) • JI Case MS1206 (Powergard PFT) • JI Case MS1207 • JI Case MS1209 (HyTran Ultra or MultiTran) • JI Case MS1210 • JI Case MS-1216 • JI Case MS-1230 (Poclairn Equipment) • JI Case MS-1317 • John Deere J20A • John Deere J20B • John Deere J20C • John Deere J20D • John Deere J14A-C • John Deere JTD 303 • John Deere J21A • Kioti • Komatsu KES 07.866, AXO80 • Komatsu-Dresser B06.0002 • Kubota UDT • Kubota Super UDT • Kubota Super UDT2 • Landini • MF 1103A & B • MF M1110 • MF 1127, 1127 A&B • MF M1129, M1129A (Permatran) • MF M1135 (Permatran III) • MF M1138 • MF M1139 (STOU) • MF M1141 • MF M1143 • MF M1144 (STOU) • MF M1145 • Parker (Denison UTTO) HF-0 • Parker (Denison UTTO) HF-1, HF-2 • Quatrol • Renk-Doromat 87.3 & 874A/B • Sauer Sunstrand/Danfoss & Hydro Static Trans Fluid • Sperry Vickers/Eaton I-286S Industrial Hydraulics • Sperry Vickers/Eaton M2950S Mobil Hydraulics • Steiger HTF (SEMS 17001) • Valmet • Valtractores • Valtra G2-08 & G2-B10 • Versatile Gear and HydrTrans Fluid • Vickers 35VQ25 • Volvo WB101 (VCE97303), except for motor grader rear axle • Volvo VCE 1273.03 • Wet brake applications • White/Minneapolis-Moline/Oliver/New Idea 55, 5J, Q-1705, Q-1722, Q-1766, Q-1766B, Q-1802, Q-1826 • Yanmar • 23M & 24M

### Product Packaging

5200709 4 -4X4L

5200709 10 – 10L

5200709 20 -20L

5200709 204 -204L

Disclaimer: The information contained in this document is based upon data believed to be reliable and relates only to the matters specifically mentioned in this document. Although DYNAMIC KOTE motor oil has used reasonable skill and care in the preparation of this information as of the date below, in the absence of any overriding obligations arising under a specific contract to supply goods or services: no representation, warranty (express or implied), or guarantee is made as to the suitability, accuracy, reliability or completeness of the information; nothing in this document shall reduce the user's responsibility to satisfy itself as to the suitability, accuracy, reliability, and completeness of such information for its particular use; there is no warranty against intellectual property infringement; and DYNAMIC KOTE motor oil shall not be liable for any loss, damage or injury that may occur from the use of this information other than death or personal injury caused by its negligence. No statement shall be construed as an endorsement of any product or process. For greater certainty, before use, particularly if the product is used for a purpose or under conditions which are abnormal or not reasonably foreseeable, this information must be reviewed with the supplier.

Τα άνωθι χαρακτηριστικά αντιπροσωπεύουν τυπικές τιμές.

DYNAMIC KOTE : 01.04.15

© copyright DYNAMIC KOTE motor oil motor oil-DYNAMIC KOTE LUBRICANTS P.C. – OT2B Industrial Zone of ALEXANDROYPOLIS – Greece (Hellas) - GR-68100 – website:

[www.dynackote.eu](http://www.dynackote.eu)





Property	Method	Unit	20W-30	10W-30
SAE			20W-30	10W-30
Specific Gravity 15°C	ASTM D 1298	kg/L	0,88	0,875
Viscosity at 40°C	ASTM D 445	cSt	85	70
Viscosity at 100°C	ASTM D 445	cSt	9,3 – 12,5	9,3 – 12,5
Viscosity Index	-	cSt	>110	>125
Pour Point	ASTM D 97	°C	<-30	<-30
Flash Point	ASTM D 92	°C	>215	>215
Total Base Numb	ASTM D 2896	mgKOH/g	>8,5	>8,5

Disclaimer: The information contained in this document is based upon data believed to be reliable and relates only to the matters specifically mentioned in this document. Although DYNAMIC KOTE motor oil has used reasonable skill and care in the preparation of this information as of the date below, in the absence of any overriding obligations arising under a specific contract to supply goods or services: no representation, warranty (express or implied), or guarantee is made as to the suitability, accuracy, reliability or completeness of the information; nothing in this document shall reduce the user's responsibility to satisfy itself as to the suitability, accuracy, reliability, and completeness of such information for its particular use; there is no warranty against intellectual property infringement; and DYNAMIC KOTE motor oil shall not be liable for any loss, damage or injury that may occur from the use of this information other than death or personal injury caused by its negligence. No statement shall be construed as an endorsement of any product or process. For greater certainty, before use, particularly if the product is used for a purpose or under conditions which are abnormal or not reasonably foreseeable, this information must be reviewed with the supplier.

Τα άνωθι χαρακτηριστικά αντιπροσωπεύουν τυπικές τιμές.

DYNAMIC KOTE : 01.04.15

© copyright DYNAMIC KOTE motor oil motor oil-DYNAMIC KOTE LUBRICANTS P.C. – OT2B Industrial Zone of ALEXANDROYPOLIS – Greece (Hellas) - GR-68100 – website: [www.dynamickote.eu](http://www.dynamickote.eu)

